

## ZUMINOL SOLUTION

# ZUMINOL SOLUTION GEAR GL-5 80W90

ZUMINOL SOLUTION GEAR GL-5 80W90 is formulated according to the latest phosphor - sulphur technology. Offering exceptional resistance to oxidation and corrosion and maximizing performance under adverse loading and temperature conditions. Seals are not affected by this product.

ZUMINOL SOLUTION GEAR GL-5 80W90 is suitable for hypoid gear, drive axle and final operating under high speed/ shock loads in trucks, construction equipment and passenger cars. Suitable for gear boxes where API GL-5 gear oil specification is recommended.

### SPECIFICATION LEVEL OR PERFORMANCE

- API GL-5
- MIL-L-2105 D
- MAN 342
- ZF TE-ML 05A / 12E/ 16B/ 17B/ 19B / 21A

### TYPICAL CHARACTERISTICS

Test	Unit	Average result
Density at 15°C	kg/l	0,893
Viscosity at 40°C	mm <sup>2</sup> /s	150,50
Viscosity at 100°C	mm <sup>2</sup> /s	15,20
Viscosity Index		102
Flash Point COC	°C	214
Pour Point	°C	-27

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*