

ZUMINOL SOLUTION

PRO 5W30 FULLY SYNTHETIC MOTOR OIL

CONTAINS PAO

ZUMINOL SOLUTION PRO 5W-30 is a fully synthetic motor oil, and contains PAO. Provided an extremely quick and stable lubricant film at the cold start and maintains this film at high temperatures, while at the same time, friction is reduced to a minimum.

ZUMINOL SOLUTION PRO 5W-30 can be used in gasoline, diesel engines of passenger cars and light duty commercial vehicles. It is formulated to meet the most demanding VW specifications available today - VW 504.00 and 507.00. It is also suitable for cars where formerly VW specifications like 503.00, 506.00, 506.01, 505.01, 502.00, 500.00, 501.01 and 505.00 are prescribed. Further tests proved that the product meets the specification MB 229.51; this oil is therefore not only universally applicable for Volkswagen, but also for Mercedes.

SPECIFICATION LEVEL OR PERFORMANCE

- BMW: LONGLIFE-04
- API SN/CF
- MB: 229.51/ 229.31
- VW: 504 00/507 00
- ACEA A3/B4, C2, C3

TYPICAL CHARACTERISTICS

Test	Unit	Average result
Density at 15°C	kg/l	0,851
Viscosity at -30°C	mPas	5950
Viscosity at 40°C	mm ² /s	69,20
Viscosity at 100°C	mm ² /s	12,00
Viscosity Index		171
Flash Point COC	°C	230
Pour Point	°C	-42
Total Base Number	mgKOH/g	6,7
Sulphate Ash	%	0,67

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.