

ZUMINOL CROSS WAY

5W50 4T ESTER BASE

High performance 100% fully synthetic lubricant for four-stroke motorcycles formulated with synthetic base oils combined with most modern additives from the market. With this selection of materials we obtain a high performance lubricant with towering performances for the latest generation of 4-stroke engines of motorcycles, especially for use in competition and for heavy conditions.

The new generation of fully synthetic engine oil achieves the following properties: a high and stable viscosity index, optimal friction characteristics, a very strong protection against wear, friction, high temperatures, corrosion and foaming and a very good detergency and dispersion. It had good low temperature performance facilitating cold start. It gives excellent results in terms of levels of acceleration. It has excellent detergency and dispersion.

SAFETY / HEALTH

Security data sheet are available upon request and should be consulted for more appropriate information. Avoid used oil contact with the skin. In case that contact occurs, rinse with water and soap. Dispose of used oil in accordance with local laws. Safety data sheet available for professional user on request. The company shall not be liable for any damages caused by misuse, or if precautions are not taken.

SPECIFICATION LEVEL OR PERFORMANCE

- API SM
- 4T JASO MA2 (T903:2006)
- 4T JASO MA

TYPICAL CHARACTERISTICS

Test	Unit	Average result
Grade SAE		5W50
Viscosity at - 30°C	mPas	6500
Viscosity at 40°C	mm ² /s	110,20
Viscosity at 100°C	mm ² /s	17,30
Viscosity Index min.		160
Flash Point	°C	242
Pour Point	°C	-24
Total Base Number	mgKOH/g	7,7
Sulphate Ash	%	0,94

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.