

ZUMINOL CROSS WAY

Ceramic 5W30 VW504.00/507.00

FULLY SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils with the excellent Ceramic Boron added. It is specifically formulated to meet the most demanding VW specifications available today - VW 504.00 and 507.00 - as well as the Long Life III requirements of the VAG Group. It is a Mid SAPS oil which meets Euro 4 and Euro 5 norms and provides protection to the Diesel Particulate Filter.

APPLICATIONS

Backwards compatible: 504.00 and 507.00 supersedes all previous VW specifications (502.00, 503.00, 503.01, 505.00, 506.00 and 506.01). All vehicles in the VAG Group (Volkswagen, Audi, Seat, Skoda) with extended oil drain intervals (30.000 km or 2 years) from 2007 onwards. Note: For V10 TDI and 5-cylinder 2.5 TDI engines, prior to 2007, where the 506.01 specification has to be used, this oil is not recommended. The first generation engines with pump injector units should use the 505.01 specification. Meets all engine protection requirements of ACEA C2.

APPROVALS

- VW 504.00/507.00

PERFORMANCE LEVEL OF BASE OIL

- ACEA C3-10
- ACEA C2
- API SN
- MB 229.51
- PORSCHE C30
- BMW LONG-LIFE 04

FEATURES

Aftertreatment protection : full aftertreatment system protection.
Total engine protection : outstanding engine cleanliness and durability.
Fuel economy : lower fuel consumption and CO2 emissions.

TYPICAL CHARACTERISTICS

Test	Unit	Average result
Density at 15°C	kg/l	0,851
Viscosity at -30°C	mPas	5950
Viscosity at 40°C	mm ² /s	69,20
Viscosity at 100°C	mm ² /s	12,00
Viscosity Index		171
Flash Point COC	°C	230
Pour Point	°C	-42
Total Base Number	mgKOH/g	6,7
Sulphate Ash	%	0,67

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.