

ZUMINOL CROSS WAY

Ceramic Infinity

FULLY SYNTHETIC MOTOR OIL.

This is a full synthetic lubricant based on carefully selected very high quality base oils. It is formulated with excellent additives to meet the demanding requirements of the VW 505.01 specification in terms of resistance to oxidation, oil thickening and the formation of sludge in the engine. It is a Mid SAPS oil (sulfated ash, phosphorus and sulfur content), which corresponds to Euro 4 and Euro 5 norms.

It provides reliable protection of after-treatment devices and Diesel Particulate Filters with the Ceramic Boron added. The oil is very universal in use and can be used for petrol and diesel engines.

APPLICATIONS

Specifically recommended for the lubrication of all TDI engines with pump injectors and for Common Rail turbodiesel engines. Ceramic Infinity is also perfect for the lubrication of the latest generation Petrol cars.

PERFORMANCE LEVEL OF BASE OIL

- ACEA: C3-12
- API: SN/CF
- BMW: LONGLIFE-04
- FORD: WSS-M2C917-A
- MB: 226.5
- MB: 229.31
- MB: 229.51
- GM dexos 2
- PORSCHE: A40
- RENAULT: RN 0700
- RENAULT: RN 0710
- VW: 502 00
- VW: 505 00
- VW: 505 01
- FIAT: 9.55535-S2

FEATURES

Aftertreatment protection: full aftertreatment system protection.

Total engine protection: outstanding engine cleanliness and durability.

Fuel economy: superior fuel economy and CO2 reduction.

TYPICAL CHARACTERISTICS

Test	Unit	Average result
Density at 15°C	kg/l	0,850
Viscosity at -30°C	mPas	5500
Viscosity at 40°C	mm ² /s	82,80
Viscosity at 100°C	mm ² /s	14,00
Viscosity Index		175
Flash Point COC	°C	232
Pour Point	°C	-42
Total Base Number	mgKOH/g	7,4
Sulphate Ash	%	0,77

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.