

ZUMINOL SOLUTION

ZUMINOL SOLUTION CRX SX 5W40

The Ceramic CRX SX 5W40 motor oil is a ceramic synthetic 5W40 oil ready for use forms a unique composition which outperforms the properties of similar oils. The ceramic components make sure that high temperatures and pressure are resisted inside the engine. Also a low friction and wear coefficient is typical for this oil. The advantages of using the ceramic oils are summarized below:

- Significant lower fuel and oil consumption
- Increase of power
- Reduction of engine noise and internal friction
- Cleaner engine
- Improved cold start

APPLICATIONS

This is a universal, ester fortified, synthetic motor oil. This Oil is specially developed for passenger car engines. Moreover this lubricant is very suitable for use in petrol and diesel engines, with or without turbo-charging with or without DPF (Diesel particulate filter).

SPECIFICATION LEVEL OR PERFORMANCE

- ACEA A3/B3,A3/B4
- API SP, API SN PLUS
- MB 229.3/229.5
- VW 502.00/505.00
- OPEL GM-LL-B-025
- PORSCHE A40
- BMW LONGLIFE-01

TYPICAL CHARACTERISTICS

Test	Unit	Average result
Density at 15 °C	kg/l	0.850
Viscosity -30 °C	mPas	5500
Viscosity 40 °C	mm ² /s	82.80
Viscosity 100 °C	mm ² /s	14.00
Viscosity Index		175
Flash Point COC	°C	232
Pour Point	°C	-42
Total Base Number	mgKOH/g	7.4
Sulphate Ash	%	0.77

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.