

ZUMINOL SOLUTION

ZUMINOL SOLUTION GEAR GL-5 80W140

ZUMINOL SOLUTION GEAR GL-5 80W140 is formulated according to the latest phosphor - sulphur technology. Offering exceptional resistance to oxidation and corrosion and maximizing performance under adverse loading and temperature conditions. Seals are not affected by this product.

ZUMINOL SOLUTION GEAR GL-5 80W140 is suitable for hypoid gear, drive axle and final operating under high speed/ shock loads in trucks, construction equipment and passenger cars. Suitable for gear boxes where API GL-5 gear oil specification is recommended.

SPECIFICATION LEVEL OR PERFORMANCE

- API GL-5
- MIL-L-2105 D
- MAN 342
- ZF TE-ML 05A / 07A/ 12E/ 16B/ 16C/16D/17B/ 19B

TYPICAL CHARACTERISTICS

| Test | Unit | Average result |
|--------------------|--------------------|----------------|
| Density at 15°C | kg/l | 0,900 |
| Viscosity at 40°C | mm ² /s | 205 |
| Viscosity at 100°C | mm ² /s | 29,70 |
| Viscosity Index | | 186d |
| Flash Point COC | °C | 215 |
| Pour point | °C | -39 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.