

ZUMINOL SOLUTION

ZUMINOL SOLUTION GEAR GL-5 LSD 85W140

ZUMINOL SOLUTION GEAR LSD GL-5 85W140 is an API GL-5 gear oil with special 'limited slip' inhibitors for hypoid drives and limited slip differentials. Also suitable for equipped with multi-disc clutches, in passenger cars, commercial vehicles, tractors and earthmoving equipment.

ZUMINOL SOLUTION GEAR LSD GL-5 85W140 is based on a formulation, which improves the frictional characteristics and which has limited slip properties. It has optimum protection against oxidation, corrosion and rust and helps extend gear life. Moreover, the product has an excellent low temperature fluidity for an optimum performance during all seasons.

SPECIFICATION LEVEL OR PERFORMANCE

- API GL-5
- MIL-L-2105D
- ZF TE-ML 05C/12C/16E
- MT-1
- Case MS 1317

TYPICAL CHARACTERISTICS

Test	Unit	Average result
Density at 15°C	kg/l	0,903
Viscosity at 40°C	mm²/s	378,80
Viscosity at 100°C	mm²/s	27,60
Viscosity Index		99
Flash Point COC	°C	245
Pour point	°C	-15

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.