

## **ZUMINOL CROSS WAY**

# Double Ester 5w30

### FULLY SYNTHETIC MOTOR OIL.

A universal, ester fortified, synthetic motor oil developed according the most recent technology and based on specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### SPECIFICATION LEVEL OR PERFORMANCE

- ACEA C3-12
- API SN
- MB 229.51/229.52
- VW 502.00/505.00/505.01
- BMW Longlife-04
- Dexos 2

### **TYPICAL CHARACTERISTICS**

Test	Unit	Average result
Density at 15°C	kg/l	0,850
Viscosity at -30°C	mPas	3750
Viscosity at 40°C	mm²/s	56,80
Viscosity at 100°C	mm²/s	10,65
Viscosity Index		181
Flash Point COC	°C	218
Pour Point	°C	-42
Total Base Number	mgKOH/g	7,2

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.