

ZUMINOL SOLUTION

ZUMINOL SOLUTION CRX 5W40

The Ceramic 5W40 motor oil is one of the latest generations of engine oil and contains a unique formula. The high tech additives guarantee low friction since the engine oil is ceramic based. The pure ceramic performance is based on the extremely resistant protective film which reduces wear and friction and resists the highest temperatures.

It is a Mid SAPS oil (sulfated ash, phosphorus and sulfur content), which corresponds to Euro 4 and Euro 5 norms. It provides the highest protection of after-treatment devices and Diesel Particulate Filters. the oil is very universal in use and can be used for petrol and diesel engines.

SPECIFICATION LEVEL OR PERFORMANCE

- ACEA C3-12
- API SN/CF
- BMW LONGLIFE-04
- FORD WSS-M2C917-A
- MB 226.5
- MB 229.31
- MB 229.51
- GM dexos 2
- PORSCHE A40
- RENAULT RN 0700
- RENAULT RN 0710
- VW 502 00
- VW 505 00
- VW 505 01
- FIAT 9.55535-S2

TYPICAL CHARACTERISTICS

Test	Unit	Average result
Density at 15 °C	kg/l	0.850
Viscosity -30 °C	mPas	5500
Viscosity 40 °C	mm ² /s	82.80
Viscosity 100 °C	mm ² /s	14.00
Viscosity Index		175
Flash Point COC	°C	232
Pour Point	°C	-42
Total Base Number	mgKOH/g	7.4
Sulphate Ash	%	0.77

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.